

CIRCOLO  
BOLLARD

6" DIA SQ  
36" H



ILLUMINATE YOUR LANDSCAPE, PATHWAYS, ENTRANCES AND OTHER OUTDOOR AREAS WITH THESE STYLISH UL WET  
Labeled BOLLARDS. THREE FEET TALL AND MADE FROM SOLID BRASS, THESE BOLLARDS ARE OFFERED IN TWO  
DESIGNS, MULTIPLE FINISHES AND ENERGY-EFFICIENT LAMPING OPTIONS. BOLLARDS SHOWN IN BLACKENED BRASS.





BOYD  
EXTERIOR

EIO262

TWILIGHT/CIRCOLO BOLLARDS

Required information for all fixture orders

Product Number / Name	Product Information	1 Lamping, Lamp Type	2 Other Requirements	3 Finish
<p>EIO242 <b>Twilight Bollard</b></p> 	<p><u>Height</u> 36" 914 mm</p> <p><u>Width</u> 6" square 152 mm</p> <p><u>Net Wt.</u> 45 lbs 20.4 kg</p> <p><b>Other Information:</b> UL listed (or equivalent) for wet locations Top: solid metal with continuing design motif Side diffusers: white acrylic</p> <p>Bollards are supplied with anchor/bolt-down plates. Footings supplied by others as required by local building codes.</p> <p><b>GSA</b></p>	<ul style="list-style-type: none"> <li>Fluorescent One, CFTR26W/GX24q (Outdoor rated at -17°C)</li> <li>HID - Ceramic Metal Halide One, CMH20W/PGJ5 (Outdoor rated at -30°C)</li> </ul> <p>Upcharges will apply for fluorescent dimming. Contact your local Boyd rep with the specification of the dimming control system being used.</p>	<p>FLO/HID Voltage:</p> <ul style="list-style-type: none"> <li>120</li> <li>277</li> </ul> <p><i>Optional:</i></p> <ul style="list-style-type: none"> <li>House side shields</li> </ul>	<ul style="list-style-type: none"> <li>Blackened Brass (BK/BS)</li> <li>Satin Brass (S/B)</li> <li>Satin Nickel (S/N)</li> <li>Black Granite (B/GR)</li> <li>Cinnamon Bronze (C/BZ)</li> <li>Silver Fog (SF)</li> </ul>
<p>EIO262 <b>Circolo Bollard</b></p> 	<p><u>Height</u> 36" 914 mm</p> <p><u>Width</u> 6" square 152 mm</p> <p><u>Net Wt.</u> 45 lbs 20.4 kg</p> <p><b>Other Information:</b> UL listed (or equivalent) for wet locations Top: solid metal with continuing design motif Side diffusers: white acrylic</p> <p>Bollards are supplied with anchor/bolt-down plates. Footings supplied by others as required by local building codes.</p> <p><b>GSA</b></p>	<ul style="list-style-type: none"> <li>Fluorescent One, CFTR26W/GX24q (Outdoor rated at -17°C)</li> <li>HID - Ceramic Metal Halide One, CMH20W/PGJ5 (Outdoor rated at -30°C)</li> </ul> <p>Upcharges will apply for fluorescent dimming. Contact your local Boyd rep with the specification of the dimming control system being used.</p>	<p>FLO/HID Voltage:</p> <ul style="list-style-type: none"> <li>120</li> <li>277</li> </ul> <p><i>Optional:</i></p> <ul style="list-style-type: none"> <li>House side shields</li> </ul>	<ul style="list-style-type: none"> <li>Blackened Brass (BK/BS)</li> <li>Satin Brass (S/B)</li> <li>Satin Nickel (S/N)</li> <li>Black Granite (B/GR)</li> <li>Cinnamon Bronze (C/BZ)</li> <li>Silver Fog (SF)</li> </ul>